Attorney Docket No. 10559-350001
Application No. 09/662,054
Amendment dated December 4, 2003
Reply to office action dated October 6, 2003

Amendment to the Claims:

This listing of claims replaces all prior versions, and

listings, of claims in the application:

1.   (Currently amended) A system, comprising:

a data source, having a plurality of different lines;

a plurality of programmable delay elements, each coupled to

one of said plurality of lines, to control a delay in said one

of said lines to produce delayed values; and

a register, storing values for said programmable delay

elements which respectively control an amount of delay caused by

said delay elements;

an arbitration logic, coupled to said plurality of delayed

values, and operating to determine relative timing of said

plurality of lines, wherein said arbitration logic includes a

first element which produces a set of first values for said

register, and a second element which determines relative arrival

of signals based on said first values, and wherein said

arbitration logic dithers between different sets of values, and

determines which of said plurality of values produces a best

desired result, and stores said best result.

2

Attorney Docket No. 10559-350001
Application No. 09/662,054
Amendment dated December 4, 2003
Reply to office action dated October 6, 2003

A1

2.   (Original) A system as in claim 1, wherein there are
one of said programmable delay elements for each of said
plurality of lines.

3.   (Original) A system as in claim 1, wherein said
register stores a plurality of values, each of said plurality of
values controlling one of said programmable delay elements.

4.   (Original) A system as in claim 3, further comprising
a non volatile memory, storing said plurality of values.

5-7. (Cancelled)

8.   (Original) A system as in claim 1, further comprising
a graphics device, and wherein said signals are from said
graphics device.

9.   (Original) A system as in claim 1, further comprising a
non-volatile memory, storing values for said delay elements, and
loading said values into said register at a specified time.

10.   (Cancelled)

3

11.   (Currently amended) A system as in claim [[10]] 1,

wherein said best result is one where the plurality of delayed

signals are received at substantially the same time.

12.   (Original) A system as in claim 10, wherein said best

result is one where the plurality of delayed signals are

received at a time skew that allows certain logic elements to

operate correctly.

13.   (Currently amended) An electronic device, comprising:

a first device producing a plurality of first outputs;

a plurality of programmable delay elements, each of said

plurality of programmable delay elements connected at one end to

one of said plurality of outputs and each producing a second

output which is delayed relative to said first outputs;

a levelization register, storing a plurality of values,

said values each individually controlling one of said delay

elements to control an amount of delay caused by said delay

element to one of said plurality of outputs; and

arbitration logic, connected to each of said second

outputs, and determining a relative delay among said second

outputs, and wherein said arbitration logic is responsive to a

4

Attorney Docket No. 10559-350001
Application No. 09/662,054
Amendment dated December 4, 2003
Reply to office action dated October 6, 2003

system event flag, which indicates a specified event in the

system.

14 - 15.   (Canceled)

16.   (Currently amended) A device as in claim [[15]] 13,
wherein said specified event is a hardware change.

17.   (Currently amended) A device as in claim [[15]] 13,
wherein said specified event is a system crash.

18.   (Currently amended) A system as in claim [[15]] 13,
wherein said arbitration logic is responsive to said flag to
produce a first multiple sets of values for said levelization
register, command said first device to produce said signals for
each of said sets of values, and determine a relative delay
among said signals based on said first sets of values and stores
a best set of values as levelization values.

19.   (Currently amended) A system as in claim [[14]] 13,
further comprising a non volatile memory which stores
levelization values, said arbitration logic storing said
levelization values in said non volatile memory.

5

A|

20.   (Currently amended) A system as in claim [[15]] 13,
further comprising, at initial system start up, downloading
values from said non volatile memory to said levelization
register.

21.   (Currently amended) A system as in claim [[15]] 13,
wherein said programmable delay elements are phase locked loops.

22.   (Currently amended) A method comprising:
receiving a plurality of signals from an external device,
each of said plurality of signals related to each other; and
      programmably delaying some of said signals relative to
others of said signals according to prestored values; and
      determining if a system event has occurred, and storing new
delay values in said non volatile memory responsive to said
system event occurring.

23.   (Original) A method as in claim 22, wherein plurality
of signals are signals from a bus.

24.   (Original) A method as in claim 23, wherein said
plurality of signals are signals from a graphics bus.

6

25.   (Original) A method as in claim 22, wherein said delaying comprises storing delay values in a non volatile memory; and

A1

using said values in said non volatile memory to adjust a value of a programmable delay element.

[[25]] 26.   (Cancelled)

[[26]] 27.   (Currently amended) A method as in claim 25 wherein said system event is a change in system hardware configuration.

[[27]] 28.   (Currently amended) A method as in claim [[25]] 26, wherein said system event is a system crash.

[[28]] 29.   (Currently amended) A method as in claim [[25]] 26, wherein said reobtaining comprises dithering sets of values in a register that stores values for said programmable delay, determining results, and accepting a set of values which have produced a specified delay.

Attorney Docket No. 10559-350001
Application No. 09/662,054
Amendment dated December 4, 2003
Reply to office action dated October 6, 2003

[[29]] 30. (Currently amended) A method as in claim [[28]] 29, further comprising storing said values in said non-volatile memory.

[[30]] 31. (Currently amended) A method as in claim [[28]] 29, wherein said specified delay is a result where there is a minimal delay between arrival of all signals.

[[31]] 32. (Currently amended) A method as in claim [[28]] 29, wherein said specified delay is a result where there is a specified delay between arrival of all signals which allows for clock skew in at least one specified logic element.

[[32]] 33. (Currently amended) A method of equalizing time delays of signals, comprising:

providing a plurality of signals which are produced in times that are synchronized with one another;

providing sets of values which represent different sets of delay values for said plurality of signals using one of said sets to delaying each of said plurality of signals by a respective amount, wherein each of said respective amounts is different then each other respective amount for a different one of said signals based on said delay values;

8

testing said signals, to determine relative amounts of

delays in said signals, to produce said delay amount;

repeating and using said testing to find a best one of said

sets; and

A1

using said delay amounts from said best one of said sets to

delay said signals.

[[33]] 34. (Currently amended) A method as in claim [[32]]

33, wherein said plurality of signals are signals from a

graphics processing device.

[[34]] 35. (Currently amended) A method as in claim [[32]]

33, wherein said delaying comprises delaying each of the signals

by respective amounts which causes them to arrive at a specified

location at substantially similar times.

[[35]] 36. (Currently amended) A method as in claim [[32]]

33, wherein said delaying comprises delaying said signals by

specified amounts which causes them to arrive at said location

at specified times which are skewed relative to one another,

wherein said skew is related to a clock margin of a system.

[[36]] 37. (Currently amended) A method of setting delays

in a system, comprising:

9

Attorney Docket No. 10559-350001
Application No. 09/662,054
Amendment dated December 4, 2003
Reply to office action dated October 6, 2003

A1

storing values indicative of time delays in a register,

said time delays representing delays to be applied to signals to

obtain a specified result;

detecting a system event which indicates that said time

delays should be changed;

when said <u>system</u> event is not detected, using said values

in said register to cause signal delays, by applying said values

to respective programmable delay elements; and

<u>only</u> when said <u>system</u> event is detected, using a logic

element to determine new delay values and applying said new

delay values to said programmable delay elements to cause signal

delays based on said new delay values.

[[37]] <u>38</u>. (Currently amended) A method as in claim [[36]]

<u>37</u>, wherein said using comprises applying a plurality of delay

values to a plurality of respective programmable delay elements

to thereby delay a plurality of lines.

[[38]] <u>39</u>. (Currently amended) A method as in claim [[36]]

<u>37</u>, further comprising storing said new delay values in a non-

volatile memory.

10

[[39]] <u>40</u>. (Currently amended) A method as in claim [[36]] <u>37</u>, wherein said system event includes a change of system components.

A\

[[40]] <u>41</u>. (Currently amended) A method as in claim [[36]] <u>37</u>, wherein said system event is an operating system crash.

[[41]] <u>42</u>. (Currently amended) A method, comprising:

receiving a plurality of signals in parallel from a specified device, which signals are produced at substantially synchronized times;

applying said plurality of said signals to programmable delay devices which allow individual delay of said signals; and

controlling said plurality of programmable delay devices to allow the signals to arrive to at least one specified location in a specified way<u>; and</u>

<u>wherein said specified way is that said signals are have a specified relationship to one another at said at least one specified location, which specified relationship is not synchronized, to allow a system to work properly</u>.

[[42]] <u>43</u>. (Cancelled)

[[43]] <u>44</u>.   (Cancelled)

[[44]] <u>45</u>.   (Currently amended) A method as in claim [[41]] <u>42</u>, further comprising storing said information in a non-volatile memory.

46.   (New) A system as in claim 1, further comprising a system event detector which produces a system event notification responsive to a specified event in the system; and

wherein said arbitration logic operates to determine said values only responsive to said system event detector.

47.   (New) A system as in claim 46, wherein said system event is a change in hardware.